



Ball Bearing with Poly Acetyl Outer, IMS Unground Inner & Carbon Balls




Ball Bearing with Poly Acetyl Outer, En-31/SAE 52100 Grinded Inner with Carbon Balls



Ball Bearing with Poly Acetyl Outer, Polyoxetal Inner with HCFC Balls



Ball Bearing with Poly Acetyl Outer, Stainless Steel Inner with Stainless Steel Balls



Ball Bearing with Poly Acetyl Outer, Poly Acetyl Inner with Stainless Steel Balls



Ball Bearing with Poly Acetyl Outer, Poly Acetyl Inner with Glass Balls

d mm	D mm	W mm	Bearing Number	Admissible load		Speed	
				POM P _{gr.} N	W 1.4401 P _{stat.} N	W 1.4401 P _{dyn} N	
5	16	5	625	45	77	56	MS Unground Inner With Carbon Balls
6	19	6	626	45	117	88	
7	22	7	627	60	153	115	
8	22	7	608	60	153	115	
9	24	7	609	70	186	139	
9	26	8	629	75	221	166	
10	26	8	6000	95	221	166	
10	28	8	16100	100	221	166	
10	30	9	6200	140	291	218	
10	35	11	6300	185	390	293	
12	28	8	6001	110	265	199	
12	30	8	16101	115	265	199	
12	32	10	6201	150	345	258	
12	37	12	6301	210	475	356	
15	32	8	16002	130	319	239	
15	32	9	6002	130	319	239	
15	35	11	6202	170	423	317	
15	42	13	6302	240	605	453	
17	35	8	16003	160	364	273	
17	35	10	6003	165	364	273	
17	40	12	6203	215	540	405	
17	47	14	6303	300	728	546	
20	42	8	16004	195	462	346	
20	42	12	6004	200	752	429	
20	47	14	6204	275	741	556	
20	52	15	6304	355	956	717	
25	47	8	16005	210	527	395	
25	47	12	6005	240	663	497	
25	52	15	6205	315	904	678	
25	62	17	6305	405	1300	975	
30	55	9	16006	245	832	624	
30	55	13	6006	280	904	678	
30	62	16	6206	385	1274	956	
35	62	9	16007	290	995	746	
35	62	14	6007	335	1170	876	

**Polyacetal Outer
With**

**MS Unground Inner
With Carbon Balls**

**En-31/SAE52100
Grinded Inner with
HCHC Balls**

**Poly Acetal Inner
With HCHC Balls**

**SS Inner with
SS Balls**

**Polyacetal resin Inner
with SS Balls**

**Polyacetal Inner with
Glass Balls**